

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claims 1, 6, 8, 22 and 27 in accordance with the following:

1. (CURRENTLY AMENDED) An apparatus to switch a paper feed direction of a paper for an image forming device having a frame, the apparatus comprising:
 - a paper feeding path of the paper;
 - a paper guide part disposed across the paper feeding path to be movable from an initial position to an operation position;
 - a supporting part to rotatably fix the paper guide part to the frame of the image forming device;
 - an elastic restoring part to restore the paper guide part from the operation position to the initial position; and
 - a restoring force blocking part to ~~block a force of~~guide the elastic restoring part so that a force of the elastic restoring part~~from acting~~ acts on the paper guide part ~~until~~only when the paper guide part fixed to the supporting part rotates beyond a predetermined angle.

2. (PREVIOUSLY PRESENTED) The apparatus according to claim 1, wherein the elastic restoring part includes an elastic spring with a first end fixed to the supporting part and a second end fixed to the frame, and the restoring force blocking part includes a movable fixing part to movably support the first end of the elastic spring to move within a predetermined range when the supporting part is rotated.

3. (PREVIOUSLY PRESENTED) The apparatus according to claim 2, wherein the movable fixing part includes a supporting groove having a circular arc shape disposed at the supporting part with respect to a center of the supporting part to move the first end of the elastic spring within the predetermined range to prevent the paper guide part from being pushed against the paper until the paper guide part is rotated beyond the predetermined angle.

4. (PREVIOUSLY PRESENTED) The apparatus according to claim 3, further comprising:

a paper sensor; and

a sensor actuator disposed at the supporting part to operate the paper sensor disposed at the frame, the paper sensor sensing whether the paper has passed through the paper guide part.

5. (PREVIOUSLY PRESENTED) The apparatus according to claim 1, further comprising a lever to rotate the paper guide part, fixed to the supporting part beyond the predetermined angle to remove a paper jam when the paper is blocked or jammed at the paper guide part.

6. (CURRENTLY AMENDED) The apparatus according to claim 45, wherein the initial position of the paper guide part is a position where the paper guide part is disposed across the paper feeding path to guide the paper to a paper duplex path of the image forming device for a duplex printing, and the paper guide part is moveable within an operation range of the paper guide part which includes a first range where the paper guide part is rotated at the predetermined angle to discharge the paper to an outside of the image forming device through the paper feeding path and a second range where the paper guide part is rotated beyond the predetermined angle in order for the lever to remove the paper jam.

7. (PREVIOUSLY PRESENTED) An apparatus comprising:
a guide to move in a working range;
a restoring unit to urge the guide to the working range when the guide is in a servicing range; and
a blocking unit to limit the working range of the guide when the guide rotates beyond a predetermined angle.

8. (CURRENTLY AMENDED) The apparatus according to claim 7, further comprising:
a developer to develop a first image on a first side of ~~the~~a paper;
a feed roller to feed the paper having the first image to the guide along a first path; and
a duplex roller to feed the paper having the first image along a second path after the paper passes the guide, wherein the developer develops a second image on a second side of the paper after being fed along the second path.

9. (PREVIOUSLY PRESENTED) The apparatus according to claim 7, wherein the working range is defined between a first position and a second position of said guide.

10. (CANCELLED)

11. (CANCELLED)

12. (CANCELLED)

13. (CANCELLED)

14. (CANCELLED)

15. (CANCELLED)

16. (CANCELLED)

17. (CANCELLED)

18. (PREVIOUSLY PRESENTED) The apparatus according to claim 9, further comprising a paper feeding path to feed a paper, wherein
said first position is a position where said guide is disposed across said paper feeding path to guide said paper before said paper contacts said guide.

19. (PREVIOUSLY PRESENTED) The apparatus according to claim 9, further comprising a paper feeding path to feed a paper, wherein
said second position is a position where said guide is disposed across said paper feeding path to guide said paper when said guide rotates to the predetermined angle.

20. (PREVIOUSLY PRESENTED) The apparatus according to claim 9, wherein
said servicing range is defined between said second position and a third position of said guide.

21. (PREVIOUSLY PRESENTED) The apparatus according to claim 20, wherein
said third position is a paper jam removing position to remove the paper when the paper is jammed.

22. (CURRENTLY AMENDED) The apparatus according to claim 9, wherein the guide is moved from the first position to the second position by a force of the paper, and from the second position to ~~the~~ a third position outside of the predetermined angle by an external force.

23. (PREVIOUSLY PRESENTED) The apparatus according to claim 20, wherein a force of said restoring unit urges the guide to move from the third position to the second position.

24. (PREVIOUSLY PRESENTED) The apparatus according to claim 23, wherein the predetermined angle corresponds to the second position.

25. (PREVIOUSLY PRESENTED) The apparatus according to claim 8, wherein the guide comprises a plurality of ribs each having a first side to guide the paper to the second path and a second side to guide the paper to an outside after the second image is developed.

26. (PREVIOUSLY PRESENTED) The apparatus according to claim 25, wherein the ribs are sloped with respect to a surface perpendicular to a feed direction of the paper.

27. (CURRENTLY AMENDED) The apparatus according to claim 23, wherein the restoring unit allows the guide to move between the first position and the third position when activated by the external ~~forces~~force, the external force including a first force moving the guide from the second position to the third position and a second force moving the guide from the third position to the first position.

28. (PREVIOUSLY PRESENTED) The apparatus according to claim 23, wherein the guide is moved from the second position to the first position only by a weight of the guide.

29. (PREVIOUSLY PRESENTED) An apparatus comprising:

a guide to guide a paper, the paper moving the guide from a first position to a second position while passing therethrough in a normal state, and the guide being moved by an external force to a third position when the paper is jammed; and

a restoring unit to urge said guide to move to the second position from the third position, and thereby to allow the guide to move from the second position to the first position by a weight of the guide.